

TYPE 45
TYPE 451



TYPE 46
TYPE 461

STANDARD TOLERANCES

U LENGTH
12" or Less ±.063
12" or Over ±.13
F LENGTH
±.25
STEM DIAMETER
±.015
BORE DIAMETER
+.005/-.003
END THICKNESS
±.063



PLUG & CHAIN
Prevent foreign matter from entering test wells when not in use. Plugs are available in Brass or Stainless Steel. A captive chain is attached to prevent loss.
To order as a test well specify plug & chain code letters after well ordering code.

CODE	PLUG & CHAIN
-BPC	BRASS
-SSPC	STN. STL.

ORDERING CODE

TW ☐☐☐–☐

CODE	U LENGTH (IN INCHES)

CODE	F LENGTH (IN INCHES)

CODE	WELL MATERIAL
P	304 STN. STL.
R	316 STN. STL.
PLorRL	304 or 316L STN. STL.
(F11)	1.25% CR. - .5 MO.
N	CARBON STEEL

CODE	THERMOWELL TYPE
45	1"FLANGE SIZE, .385"ID
46	1.5"FLANGE SIZE, .385"ID
451	1"FLANGE SIZE, .260"ID
461	1.5"FLANGE SIZE, .260"ID

The information contained hereon shall be considered the sole property of Thermo Electric Company, Inc. The recipient thereof agrees not to disclose or reproduce said information to parties outside the recipients organization without the written permission of Thermo Electric.